



An Oshkosh Corporation Company

TELESCOPIC CRANES QUICK REFERENCE GUIDE

	MODEL	MAX. LIFT CAPACITY	RATING	WEIGHT	MAX. HORIZONTAL REACH*	MAX. VERTICAL REACH**	EXTENSION	ROTATION	REQ'D MOUNTING SPACE	MIN. GVWR***
ELECTRIC	1015E	3,200 LB	10,500 FT-LB	660 LB	15'-0"	16'-1"	1 MANUAL 1 HYDRAULIC	400°	14-1/12" X 17"	11,500
	3203i	4,000 LB	12,000 FT-LB	635 LB	15'-0"	16'-2"	1 MANUAL 1 HYDRAULIC	CONTINUOUS	14" X 18"	11,500
	4004i	4,000 LB	18,000 FT-LB	758 LB	16'-0"	16'-10"	1 MANUAL 1 HYDRAULIC	CONTINUOUS	14" X 18"	15,000
	2020E	5,000 LB	20,000 FT-LB	920 LB	20'-0"	20'-11"	1 MANUAL 1 HYDRAULIC	400°	17" X 17-3/4"	15,000
	5005i	5,000 LB	30,000 FT-LB	1,440 LB	22'-0"	24'-0"	1 MANUAL 1 HYDRAULIC	CONTINUOUS	18" X 18"	18,000
	6006i	6,000 LB	38,000 FT-LB	1,450 LB	22'-0"	23'-1"	1 MANUAL 1 HYDRAULIC	CONTINUOUS	18" X 18"	18,000
HYDRAULIC	1015	3,200 LB	10,500 FT-LB	660 LB	15'-0"	16'-1"	1 MANUAL 1 HYDRAULIC	400°	14-1/12" X 17"	11,500
	2020	5,000 LB	20,000 FT-LB	920 LB	20'-0"	20'-11"	1 MANUAL 1 HYDRAULIC	400°	17" X 17-3/4"	15,000
	2820	5,000 LB	28,000 FT-LB	1,400 LB	20'-6"	22'-2"	2 HYDRAULIC	400°	20" X 21"	18,000
	6000	6,000 LB	40,000 FT-LB	1,200 LB	22'-1"	21'-10"	2 HYDRAULIC	400°	20" X 21"	19,500
	7500-22'	7,500 LB	47,000 FT-LB	1,795 LB	22'-6"	23'-10"	2 HYDRAULIC	400°	20" X 21"	19,500
	7500-30'	7,500 LB	52,000 FT-LB	2,400 LB	30'-10"	32'-1"	2 HYDRAULIC	400°	20" X 21"	19,500
	8600	8,600 LB	52,000 FT-LB	1,825 LB	22'-6"	23'-10"	2 HYDRAULIC	400°	20" X 21"	19,500
	10000-25'	10,000 LB	72,000 FT-LB	2,290 LB	24'-9"	26'-0"	2 HYDRAULIC	400°	20" X 21"	26,000
	10000-30'	10,000 LB	75,000 FT-LB	2,480 LB	30'-10"	32'-1"	2 HYDRAULIC	400°	20" X 21"	26,000
	12000-25'	12,000 LB	81,000 FT-LB	2,610 LB	24'-8"	26'-2"	2 HYDRAULIC	400°	24" X 23-3/4"	26,000
	12000-30'	12,000 LB	81,000 FT-LB	2,720 LB	30'-10"	32'-3"	2 HYDRAULIC	400°	24" X 23-3/4"	26,000
	14000-25'	14,000 LB	95,000 FT-LB	3,100 LB	24'-5"	26'-3"	2 HYDRAULIC	400°	24" X 25"	33,000
	14000-30'	14,000 LB	94,000 FT-LB	3,280 LB	31'-0"	32'-3"	2 HYDRAULIC	400°	24" X 25"	33,000

*Flip sheave up (From centerline of rotation)

** From mounting surface

***The gross vehicle weight rating (GVWR) is a minimum guideline. Contact IMT if you have questions regarding your particular installation.

