



An Oshkosh Corporation Company



# DOMINATOR<sup>®</sup> I

## Mechanics Body

With enhanced strength and stability for higher crane loads, numerous configuration possibilities, and a body rating of 52,000 ft-lb (7.9 tm), the Dominator I mechanics truck offers exceptional performance in virtually any industry. With the Dominator I mechanics truck, you don't have to bring your equipment into the shop for service, because the shop comes to you.

### > BASE BODY SPECIFICATIONS

<b>Body Size</b>	9' (2.7 m)	9' (2.7 m)	11' (3.4 m)	11' (3.4 m)	11' (3.4 m)	11' (3.4 m)	11' (3.4 m)	11' (3.4 m)
<b>Body Configuration<sup>4</sup></b>	LH & RH STD	RF RSD	LH & RH STD	RF RSD	LF RSD	LF & RF STD	LH AR, RF RSD	ALL RSD
<b>Body Rating</b>	52,000 ft-lb (7.9 tm)	52,000 ft-lb (7.9 tm)	52,000 ft-lb (7.9 tm)	52,000 ft-lb (7.9 tm)	52,000 ft-lb (7.9 tm)	52,000 ft-lb (7.9 tm)	52,000 ft-lb (7.9 tm)	52,000 ft-lb (7.9 tm)
<b>Body Weight<sup>1,3</sup></b>	2728 lb (1237.4 kg)	2806 lb (1272.8 kg)	3103 lb (1407.5 kg)	3212 lb (1456.9 kg)	3212 lb (1456.9 kg)	3317 lb (1504.6 kg)	3495 lb (1585.3 kg)	3495 lb (1585.3 kg)
<b>Body Width</b>	96" (2.4 m)	96" (2.4 m)	96" (2.4 m)	96" (2.4 m)	96" (2.4 m)	96" (2.4 m)	96" (2.4 m)	96" (2.4 m)
<b>GVWR</b>	14,000-19,500	14,000-19,500	16,000-19,500	16,000-19,500	16,000-19,500	16,000-19,500	16,000-19,500	16,000-19,500
<b>Storage Capacity<sup>3</sup></b>	97.2 ft <sup>3</sup> (2.8 m <sup>3</sup> )	104.2 ft <sup>3</sup> (2.9 m <sup>3</sup> )	120.5 ft <sup>3</sup> (3.4 m <sup>3</sup> )	131.3 ft <sup>3</sup> (3.7 m <sup>3</sup> )	131.3 ft <sup>3</sup> (3.7 m <sup>3</sup> )	142.2 ft <sup>3</sup> (4.0 m <sup>3</sup> )	142.2 ft <sup>3</sup> (4.0 m <sup>3</sup> )	166.1 ft <sup>3</sup> (4.7 m <sup>3</sup> )
<b>Angle of Departure</b>	15°	15°	15°	15°	15°	15°	15°	15°
<b>Chassis CA<sup>2</sup></b>	60" (1.5 m)	60" (1.5 m)	84" (2.1 m)	84" (2.1 m)	84" (2.1 m)	84" (2.1 m)	84" (2.1 m)	84" (2.1 m)
<b>Max. IMT Crane Model</b>	8600 22'	8600 22'	8600 22'	8600 22'	8600 22'	8600 22'	8600 22'	8600 22'

<sup>1</sup> Includes doors, side packs, workbench. <sup>2</sup> Does not include welder deck. <sup>3</sup> Body weight and storage capacity are estimated based on product configuration.

<sup>4</sup> Standard (STD) = 44", Raised (RSD) = 60"



## > STANDARD FEATURES

- IMT Patented Inverted A-Frame Design
- Three-Point Access
- Multiplex Electrical System with Programmable Logic
- IMT Compartment Coating (VOC-compliant polyurethane modified multicolor spray finish)
- Workbench Bumper



## REAR ACCESS PACKAGE

Featuring an extended handle for an easy grip and an extra step, the standard rear access package improves accessibility and is available curbside and roadside.

## > OPTIONS

- High-Intensity LED Lighting Package
- Axalta Bedliner
- IMT SiteStar® Lube Skid
- Drawer Sets, Adjustable Shelves
- Stabilizers
- Workbench Vises and Vise Plates
- Energy-Absorbing Boom Support
- Compartment Pressurization System
- Compressed Air and Welding Systems
- Headache Rack
- Telescopic Roof
- Master Locks



## HIGH-INTENSITY LED LIGHTING

LED light bars provide superior light penetration for enhanced visibility.

## > COMPATIBLE IMT CRANES

ELECTRIC		HYDRAULIC		
• 6006i	• 3203i	• 8600	• 6000	• 2020
• 5005i	• 2020E	• 7500	• 2820	• 1015
• 4004i	• 1015E			



## BODY SUBSTRUCTURE

Patented A-Frame design with integrated crane box is engineered for maximum strength and weight reduction.



**NOTHING SAYS COMMITMENT LIKE THE DIAMOND.™**



An Oshkosh Corporation Company

Iowa Mold Tooling Co., Inc. | 500 Highway 18 West | Garner, Iowa 50438 | 800-247-5958 | [imt.com](http://imt.com)

IMT reserves the right to make changes in engineering, design, and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. IMT, the IMT logo, Dominator, NOTHING SAYS COMMITMENT LIKE THE DIAMOND and SiteStar are registered trademarks or trademarks of Iowa Mold Tooling Co., Inc., Garner, IA, USA. © 2018 Iowa Mold Tooling Co., Inc. All Rights Reserved.



REV 11/18