

# SiteStar<sup>®</sup>

Lube Skid



## ► SiteStar® Lube Skid

Our lightweight IMT SiteStar lube skid easily attaches to and detaches from your mechanics truck, giving you the flexibility to provide lube truck services to your fleet.

### Product Tanks

#### Oil, Salvage, Antifreeze, Water

- Available sizes — 55-gal (208.2 L)
- Fill system — tanks are filled from a top-fill location

### Pumping Systems

- Oil — 5:1 ratio air piston pump
- Antifreeze and salvage — air diaphragm pump
- Grease — 50:1 ratio air piston pump

### Available Configurations

- 2 oil, 1 antifreeze, and 1 oil salvage
- 2 oil, 1 antifreeze, 1 oil salvage, and 1 grease (120 lb)
- 3 oil and 1 antifreeze
- 3 oil, 1 antifreeze, and 1 grease (120 lb)
- 3 oil and 1 oil salvage
- 3 oil, 1 oil salvage, and 1 grease (120 lb)
- 4 oil
- 4 oil and 1 grease (120 lb)

### Hose Reel Location

The hose reels are located on a fixed shelf on the skid that allows them to be accessed from the rear of the load-bed area.

### Skid Structure

The skid is constructed of structural tubing with 1/8" (0.32 cm) deckplate with an integral hose reel shelf at the rear and an incorporated tank containment cage.

### Product Pump Locations

Air operated piston and diaphragm pumps are located on the floor of the skid and the grease system air piston pump is located on the grease drum.

### Air Operating System

The skid has a pneumatic quick coupler for providing air to the pumping system from a remote air compressor. The pumps are activated from separate control valves for each system.

### Lifting

The skid can be removed from the load bed area with a crane or with a fork truck. There are three lift points on the skid for lifting with a crane and fork pockets in the skid for a fork truck.

### Optional Accessories

The skid has an option for final oil product filtration between the product pumps and the dispensing hose reels.

### Specifications

|                                |  |
|--------------------------------|--|
| <b>Weight:</b>                 |  |
| (4) Tanks empty without grease | 1592 lb (722.1 kg)   |
| (4) Tanks empty with grease    | 1712 lb (777 kg)   |
| (4) Tanks full without grease  | 3242 lb (1471 kg)  |
| (4) Tanks full with grease     | 3362 lb (1525 kg)  |
| <b>Height</b>                  | 54" (137.2 cm)   |
| <b>Width</b>                   | 48" (121.9 cm)   |
| <b>Length</b>                  | 7' 4" (2.3 m)  |
| <b>Capacity</b>                | 220 gal (832.8 L)  |
| <b>Type</b>                    | Removable from load bed  |
| <b>Tie-Down</b>                | D-ring tie-downs in the front and rear for fastening to load-bed tie-downs |



### Nothing Says Commitment Like The Diamond.™

IMT has been meeting the needs of our customers for over 50 years and none of it would have been possible without a distributor network that's second to none. IMT distributors offer fast, knowledgeable service and the ability to help customers find the right product for every application. When you're looking for reliable equipment and dependable service, remember IMT.



An Oshkosh Corporation Company

### Iowa Mold Tooling Co., Inc.

500 Highway 18 West  
Garner, Iowa 50438  
800-247-5958 • [www.imt.com](http://www.imt.com)

IMT reserves the right to make changes in engineering, design, and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. IMT, the IMT logo and SiteStar are registered trademarks or trademarks of Iowa Mold Tooling Co., Inc., Garner, IA, USA. NOTHING SAYS COMMITMENT LIKE THE DIAMOND is a service mark of Iowa Mold Tooling Co., Inc.  
© 2011 Iowa Mold Tooling Co., Inc. All Rights Reserved.